



1. Galvanization finish, Q235B steel, with monoplate sliding.
2. Suitable for fixing and adjustment of large power motors.

Monoplate-MP	Motor Installation Size	A	B	C	E1	E2	E3	G	H	J	K	L	M	N	O	P	R	SW	S	KG
270-63/90-MP	63-71-80-90	270	195	33	100	125	140	190	25	25	50	50	10.5	31.5	132	98	25	19	3	3.1
307-90/112-MP	90-100-112	307	213	33	140	160	190	255	32.5	25	50	50	10.5	25.5	162	108	25	19	3	4.1
340-100/132-2-MP	100-112-132	340	290	40	160	190	216	286	35	30	62	47.5	12.5	37.5	215	165	30	22	4	7.9
430-100/132-2-MP	100-112-132	430	290	40	160	190	216	286	35	30	62	47.5	12.5	37.5	215	165	30	22	4	8.9
430-160/180-2-MP	160-180	430	370	40		254	279	379	50	30	62	62	12.5	41.5	287	248	30	22	4	12
490-160/180-MP	160-180	490	370	40		254	279	379	50	30	62	62	12.5	41.5	287	248	30	22	4	12.7
490-180/200-MP	180-200	490	410	40		279	318	420	50	30	60	52	17	40.5	329	285	30	22	4	14.6
585-200/225-MP	200-225	585	450	50		318	356	468	56	30	60	52	17	49	352	300	30	22	5	23.7
600-250-MP	250	600	470	65			406	515	54.5	30	60	60	22	50.5	369	320	35	27	5	28.1
735-280-MP	280	735	570	65			457	585	64	30	70	70	22	55	460	420	35	27	5	38.2
800-315-MP	315	800	760	80			508	653	72.5	30	80	80	28		560	520	35	27	5	