



1. Made of high quality steel Q235B, supplied with matched fixing screws.
2. Suitable for fixing and adjustment of all kinds of motors

Type	Slide Length G1	Motor Type	M*h	e*s	G2	a	b	b/2	Φd	B	H1	H2	GW (kg)
312/6	240	63/71	M6*19	75*6	262	16	280	-	12	40	28	30	1.4
312/8	240	80/90	M8*27	75*6	262	16	280	-	12	40	28	30	1.5
375/6	305	63/71	M6*19	75*6	325	16	343	-	12	40	28	30	1.5
375/8	305	80/90	M8*27	75*6	325	16	343	-	12	40	28	30	1.6
375/10	305	100/112	M10*32	75*6	325	16	343	-	12	40	28	30	1.6
395/8	302	80/90	M16*28	97*8	325	20	355	-	12	50	40	43	3.4
395/10	302	100/112	M10*35	97*8	425	20	355	-	12	50	40	43	3.4
495/8	405	80/90	M8*29	97*8	425	20	456	-	12	50	40	43	4
495/10	405	100/112/132	M10*35	97*8	425	20	455	-	12	50	40	43	4
495/12	405	160	M12*49	97*8	425	20	455	-	12	50	40	43	4
530/10	413	132	M10*37	119*9	442	25	480	-	14	60	50	54	6.4
530/12	413	160	M12*49	119*9	442	25	480	-	14	60	50	54	6.4
630/10	515	132	M10*37	119*9	542	25	580	-	14	60	50	54	8.2
630/12	515	160/180	M12*45	119*9	542	25	580	-	14	60	50	54	8.2
686/12	538	160/180	M12*43	154*12	575	28	630	315	18	75	60	64	12.8
686/16	538	200/225	M16*62	154*12	575	28	630	315	18	75	60	64	12.8
864/16	700	200/225	M16*60	300*16	810	32	800	400	24	90	75	-	16.6
864/20	700	250/280	M20*68	300*16	810	32	800	400	24	90	75	-	16.6
1072/20	865	250/280	M20*77	360*19	995	36	1000	500	30	112	100	-	33.4
1072/24	865	315	M24*88	360*19	995	36	1000	500	30	112	100	-	33.4
1330/24	1065	315/355	M24*95	430*21	1215	40	1250	625	30	130	125	-	56.6